

**Options** (  Specify when ordering - ● Standard - ○ Optional)

Type	OPTILINE MP	OPTILINE PRO
Storage stands	●	●
Link between toolbar and packer roller	○	●
Automatic "A-frame" coupling	●	-
Fitting kit <sup>(1)</sup>	○	-
1 000 rpm mechanically driven fan	●	-
Hydraulically driven fan	○	●
Mechanical seed level indicator	●	●
Full-opening V-shaped hopper cover	●	●
Hopper extensions	○	○
Sieve	●	●
Peg-wheel metering and rate variator	●	●
Fan air filter	○	●
Tramlining 2 x 3 rows (2 x 2 rows standard)	○	○
ULTRON kit	○	●
ULTRON MS kit	○	○
VISION SPB kit	contact us	○
Left or right manual 1/2 width disengagement	●	●
Hectare counter	●	●
Rear pre-emergence markers	○	○
Vertical lift side markers fitted on the seed drill	●	●
Vertical lift side markers fixed on the SULKY power harrow	○	○
Full road lighting	○	○
Loading platform with folding steps	●	●
LS 2.20 drilling system (2 rows of Suffolk coulters)	<input type="checkbox"/>	-
LS 3.20 drilling system (3 rows of Suffolk coulters)	<input type="checkbox"/>	-
LS 2.30 drilling system (UNIDISC)	<input type="checkbox"/>	-
LS 2.80 drilling system (80 kg) with consolidation wheels	-	●
Hydraulic depth control (DA)	○	-
40 mm wide consolidation wheels <sup>(2)</sup>	○	-
Following harrow (straight or levelling tines)	<input type="checkbox"/>	○
Hydraulic toolbar lift (1SA)	○	-
Solo drilling kit	-	○
Rear, lateral and front reflectors	○	○

<sup>(1)</sup> provide make and model of harrow

<sup>(2)</sup> For LS 2.20 and LS 2.30 drilling systems only



An important stage in the new SULKY anti-corrosion treatment process : all components are dipped by robot into a bath of paint primer.

**Top quality paint for long-lasting protection**

All painted components are treated on the SULKY paint line. After the surfaces have undergone a five-stage cleaning and preparation process, they are dipped in a bath of high adhesion hydrosoluble primer. After baking at 130°, a second anti-corrosion primer and a top coat of polyurethane paint are applied using a spray gun before final baking at 100°.

Type	OPTILINE MP3	OPTILINE MP3.5	OPTILINE MP4	OPTILINE MP4.5	OPTILINE PRO3	OPTILINE PRO3,5	OPTILINE PRO4						
Working width	3,00 m	3,50 m	4,00 m	4,50 m	3,00 m	3,50 m	4,00 m						
Hopper capacity	750 litres / 1 100 litres <sup>(3)</sup>		1 050 litres / 1 650 litres <sup>(3)</sup>		750 litres / 1 100 litres <sup>(3)</sup>		1 050 litres / 1 650 litres <sup>(3)</sup>						
Hopper dimensions (m)	1,25 x 1,22		2,20 x 1,22		1,25 x 1,22		2,20 x 1,22						
Loading high (cm)	180												
Row spacing (cm)	15	12,5	12,5	14,3	12,5	14	13,6	15	22	26	13,3	15,4	
Number of rows	20	24	28	28	32	32	22	20	15,9	13,5	30	26	
Weight (approx <sup>(4)</sup> )	715 kg		820 kg		930 kg		1 040 kg		1360 kg		1580 kg		1700 kg

<sup>(3)</sup> with hopper extension.

<sup>(4)</sup> with basic features and a LS 3.20 toolbar (3 rows of Suffolk coulters) on OPTILINE MP and LS 2.80 on OPTILINE PRO